

NUOVA SIMONELLI · PRODUCT SHEET

Appia Life Compact

Two groups in a narrower body.

Versions: S | V

Groups: 2

Appia Life Compact is the Appia Life with two groups in a narrower body: 554 mm wide, compared with 784 mm for the standard 2-group version.

It belongs to the Appia Life STANDARD series and shares its proven features: SIS, Drytex boiler insulation, reverse mirror, push & pull steam levers and a stainless steel drip tray. You can place it where a full-size 2-group machine will not fit.

Available as semi-automatic (S) or volumetric (V) with programmable doses and automatic wash. One steam wand and a 7.5 l boiler.



Standard features

SIS - Soft Infusion System

SIS guarantees a soft infusion allowing a consistent result, it compensates for any incorrect coffee tamping and it avoids the channelling effect.

Drytex insulation

Boiler insulation that reduces 13% of energy consumption compared to the Appia II.

20% less environmental impact

New thermal system, new materials and optimised mechanical components, confirmed by Life Cycle Assessment.

Reverse mirror

Check the coffee dripping and cleanliness of the filter holder from a much more comfortable position.

Aligned cup warmer

The cup warmer is aligned with the top of the machine for an easier reach.

Push & pull levers

Push & pull steam levers and adjustable steel nozzles.

Easy maintenance

New adjustable nozzle attachment, new side opening system and redesigned groups.

Automatic wash **V ONLY**

Automatic wash function (volumetric version).

One steam wand

One steam wand.

Special order

Easycream **V ONLY**

Automatic milk frothing; optional on the volumetric version only.

Raised groups

Raised groups.

On/off electric cup warmer

On/off electric cup warmer.

Economizer

Hot water economizer.

Telemetry **V ONLY**

Telemetry.

White Pearl and Heart Red

Also available in White Pearl and Heart Red, with chrome profiling.

Technical specifications

2 GROUPS (COMPACT)

Versions	S, V
Width (cm)	55.4
Depth (cm)	54.5
Height (cm)	49.8
Net / gross weight (kg)	42.5 / 52.5
Boiler (l)	7.5
Steam wands	1
Maximum power (W)	2900
Voltage	220-240 V 50/60 Hz or 110-120 V 60 Hz

Semi-automatic (S) and volumetric (V) versions share the same dimensions and specifications.

Power supply: 220-240 V, 50/60 Hz (2900 W) or 110-120 V, 60 Hz (1400 W). Counter hole: 210 mm from the left side and 230 mm from the front.