

NUOVA SIMONELLI · PRODUCT SHEET

Appia Life XT

Even more advanced.

Groups: 2 | 3

The new XT version completes the Appia Life machines family, available in 2 and 3 groups in the volumetric version (5 dispensing keys per group).

The performance remains unchanged compared to the 2 and 3 group Appia Life models, but the Appia Life XT has evolved in the form and in the innovative details that improve the final results thanks to the TFT display, pressure sensors, led lights and telemetry.

The XT is a new Appia Life version with TFT display that grants a better user experience showing the most important data about dose program, counters, cleaning, setting and buttons and display brightness.



Standard features

TFT display

Dose program, cleaning, counters, settings, buttons and display brightness.

Pressure sensors

Read the pressure inside the boiler directly from the display.

PID

PID temperature control.

LED lights

LED lights.

5 dispensing keys per group

Volumetric version with 5 dispensing keys per group.

SIS - Soft Infusion System

Soft infusion that compensates for incorrect tamping and avoids channelling.

Drytex insulation

Boiler insulation that reduces 13% of energy consumption compared to the Appia II.

Reverse mirror

Check the coffee dripping and cleanliness of the filter holder from a more comfortable position.

Automatic cleaning

Schedule the group cleaning and set up the alarm.

Special order

Easycream

Automatic frothing for cow's milk and plant based drink, up to 4 milk frothing settings.

Cool touch steam wand

Cool touch steam wand.

Raised groups

Raised groups.

On/off electric cup warmer

On/off electric cup warmer.

Telemetry

Telemetry.

Economizer and rail

Hot water economizer and cup rail.

White Pearl and Heart Red

Also available in White Pearl and Heart Red, with chrome profiling.

Technical specifications

	2 GROUPS	3 GROUPS
Width (cm)	78.4	101.4
Depth (cm)	54.4	54.4
Height (cm)	50	50
Net / gross weight (kg)	54 / 66	72 / 85
Boiler (l)	11	15
Maximum power (W)	3150	5200
Voltage	220-240 V or 380-415 V 3N	220-240 V or 380-415 V 3N

Power supply: 2 and 3 groups: 220-240 V 50/60 Hz or 380-415 V 3N.